

## Use of Steel in Refurbishment as an Environmentally Friendly Activity

László Hegedűs

Dr., Sen. Assist. Professor, Budapest University of Technology and Economics



At the Department of Steel Structures, Technical University of Budapest, Hungary a project had been carried out aimed to refurbishment of structures.

The main aims of the project was to:

- develop a new BSc curriculum for refurbishment steelwork engineering and
- to prepare new teaching materials.

In the framework of the project the following institutions took part in:

- Technical University of Budapest, Hungary (coordinator)
- University “Federico II”, Naples, Italy
- University “Blaise Pascal”, Clermont-Ferrand, France
- Technical University of Brandenburg, Cottbus, Germany,
- Heed, Structural Design Ltd., Budapest, Hungary

The project lasted for three years.

The main activities of the project were:


- mobility of students and staff members
- one seminar with invited participants from TU Bratislava, Slovakia and TU Timisoara, Romania
- two workshops


The main results of the project are summarized in two volumes of papers and in a CD ROM with the teaching material, which is based on ESDEP (European Steel Design Education Programme), literature and the project results.

The CD ROM includes four main parts.




## BEHAVIOUR AND EFFECTS



The Use of Steel in Refurbishment 

Strengthening Options in Rehabilitation by Means of Steelworks 

Some Aspects of Fires in Buildings 

The Role of Earthquakes for the Structural Refurbishment 

Fatigue of Metallic Structures 

Corrosion and Corrosion Protection of Steel Structures 



## STRUCTURAL SYSTEMS OF REFURBISHMENT

Strengthening of structures

Transformation and repair

Re-use of buildings

Residual life assessment for bridges

Part III is the largest one. The details of the main four chapters are given below:

### Strengthening of structures

Introduction

Levels of reconstruction

Temporary works

Systems for strengthening (repair and reinforcing)

Strengthening masonry structures

Strengthening masonry structures by lateral confinement

Timber structures

Concrete structures

Iron and steel structures

Comparison of different strengthening methods of masonry structures

Strengthening with IMS system

Beam-to-column connections in refurbishment

Concluding summary

References & additional reading

### Transformation and repair

Summary

Introduction

Modifying building structures

General consideration of refurbishment

Refurbishment in seismic areas

About some principles of buildings refurbishment in seismic areas

Seismic upgrading of churches by means of dissipative devices

Case studies

The historical centre of Ancona, Italy

Van leer office building in Amstelveen, Netherlands

Office building, sea containers limited, London, Great Britain

Gymnasium in Cantu, Como, Italy

Rue de L'ourcq, Paris, France

Chemistry buildings of Technical University of Berlin, Germany

Alter Bahnhof exhibition hall, Rosenheim, Germany

Rue St. Jacques - a modern apartment above a late 19th century house

Abbey of Val Saint-Lambert Seraing, Belgium

Extension to the imperial war museum, London, Great Britain

More Italian examples

Rehabilitation of the aerial mast "Habichtsberg" In Germany

Concluding summary

References & additional reading

## Re-use of buildings

Summary

Introduction

Principles of restructuring

Case studies

Two examples of the use of steel in refurbishment at Blaise Pascal University

A proposal of refurbishment with steel at Blaise Pascal University

Working quarters at Folkwang School In Essen-Werden, Germany

Kannerland, Limpertsberg, Luxemburg

The Roemerhof In Zurich, Switzerland

Office building Amsterdam, Weteringschans 165, Netherlands

The court of justice in Ancona, Italy

Concluding summary

References & additional reading

## Residual life assessment for bridges

Summary

Introduction

General elements

Fatigue safety of existing railway bridges

Main steps for the assessment

Material identification and verification method for the residual safety of old steel bridges

Fatigue strength of riveted bridges

Inspection of bridges with orthotropic steel decks

Stress reduction due to surfacing on orthotropic steel decks

Strengthening of steel bridges

General considerations

Methods of strengthening

- Direct strengthening
- Indirect strengthening
- Rehabilitation of fatigue cracked orthotropic steel bridges

- Repair techniques for the rehabilitation of fatigue cracked orthotropic steel bridges
- Fatigue assessment of steel bridges of the bullet train system
- Orthotropic redecking of bridges
- Rehabilitation and strengthening of steel road bridges
- Steel plate bonding for concrete bridge strengthening


#### Case studies

- Angel Saligny Bridge
- Forth Bridge
- Rodenkirchen Bridge
- Eiseren Steges
- Tower Bridge
- Dismounting, transportation and rebuilding of a highway bridge
- Northumberland
- Refurbishment of Hungarian Danube Bridges
- Some examples of refurbishment in industrial steel structures and bridges
- The refurbishment of the West Railway Station
- Bearing replacement of the Petőfi bridge in Budapest
- Load test examinations on the Budapest Southern Railway bridge
- Strengthening of the deck of the Danube bridge in Ujpest


About the “Refurbishment of Hungarian Danube Bridges” during the Ariadne 11 workshop a presentation was given.

The topic of „Dismounting, transportation and rebuilding of a highway bridge” has a special interest. It is presented in details.





Usage of thermovision for diagnostic of structures 

## MANAGEMENT, DIAGNOSTIC AND MISC.


Diagnostics 


Supervision of cable structures using natural frequency as characteristic parameter 

Concurrent engineering design methodology for refurbishment of steel structures 


Two simple example how to use computer analysis in refurbishment of historical structures 


Techniques for partial demolition 

Curriculum for refurbishment steelwork engineering (Romanian proposal) 

Behaviour of structural members in case of welding under loading 

The use of swaged bolts in refurbishment 

Bridge reconstruction in Berlin 

Analysis of time-dependent temperature behaviour of welded constructions 





### 1. Dismounting, transportation and rebuilding of a highway bridge




## 1.1 Introduction

In 1988 the Hungarian Highway Authorities decided that instead of the full reconstruction of the deck plate of a 2 x 106 m span riveted truss highway bridge built in 1942 across the Tisza river at Polgár, a new bridge had to be built, just beside the old one.





The new wider and higher load capacity bridge was opened to traffic in 1990 and the old one was closed, waiting for demolition. However, due to the good condition of the steel structure the idea arose to dismount the structure and rebuild it above the same river upstream in 100 km in a place where the modest traffic requirements had already been satisfied by a floating bridge.



A permanent bridge would have meant here an achievement. The process of dismounting, transportation and rebuilding was developed and design by dr. István Szatmári, associated professor at the Department of Steel Structures, Technical University of Budapest, Hungary and the computerised supervision of the process was worked out by Miklós Kálló.


## 1.2 The project

According to the design, the two span continuous bridge was to be cut at the middle support, and the two parts (practically the two spans, 106 m long and of a mass of 430 tons each) were to be shipped on board of barges to their final place. Two barges had to be rigged specially so as to ensure the lifting, descending and horizontal movement of the spans. Four 15 m high columns were built to each barge with two cross beams between them. The beams were moveable (up and down) along the columns by hydraulic jacks and made possible the movement of the full load in 175 mm steps. The two lift barges were connected to each other by two 21.2 m long lattice girders to perform a statically stable structure. These barges were able to raise a span from the supports and let it down on the board of the transport barge at the original place and to perform the inverse operation at the final destination place.

A series of pictures illustrates some characteristic situation of the task, together with the difficulties which had to solve along the long voyage.

The whole process was finished at the end of July 1994 with full success. This delicate operation needed measurements and continuous supervision in some stages of the work. These can be detailed as follows.

**CIGÁND. The elevated span is towed to its place.**




### **1.3 The process of hoisting**

During the vertical movement of the spans the position of the four hydraulic jacks, working on the same barge and controlled by the same engineer, was measured by potentiometric transducers and displayed on screen. The display had three ranges for each transducers: a 200 mm range, which showed the actual position of the cylinder, a  $\pm 5$  mm range, which always followed the actual position and signalled the vicinity of the marked positions, where the pins (fixing the raise beams, needed for the step-by-step motions) had to be changed. This way the engineers controlling the hydraulic systems were able to see the displacements, guess the velocity and sense the critical points of the four jacks, although these were hidden by structural parts. It proved to be extremely important due to the fact that the four reaction forces were far from being equal, therefore some interaction (e. g. to slow down the motion of one cylinder or quicken an other) was needed time to time based upon the display and pressure gage readings.

### **1.4 Supervision of the whole elevating gear**

During both the vertical and the horizontal movements (latter carried on by sailors maneuvering the barges) a third computer gave a general survey of the state of operation. 36 strain gages were bonded to the chords of lattice beams between the two barges (four of them for drift control) for measurement of stresses in the critical places and two inductive transducers measured the inclination of the bridge in the longitudinal and transversal direction. The software calculated the horizontal and vertical bending moments, torsional moments, maximum stresses and the normal forces. The result could have been graphically represented on the display. As it later became clear, the display of the maximum stresses was always important, the vertical bending moment during the vertical movements and ballasting, the horizontal bending moment while the barges were moved together along the river. The normal forces – very likely due to the accurate setting of geometry – did not change too much. The inclinations showed correctly the actual position of the bridge, seldom was needed any correction.



### 1.5 Supervision of the elevated structure

The third main supervision) computer, when raising up the 2<sup>nd</sup> span at the final place, had to measure the stresses in one of the diagonals of the bridge. This very slender diagonal originally (when the span was supported at the ends) took tensile forces, while lifting the span up, the position of supports (raising beams) turned it in compression. Uprising the structure (at the first time only partly) the direction of the possible buckling became evident (as it was shown on the display), the diagonal in question was fixed by steel cable and remained so until the span was put onto its final supports.

### 1.6 Summary

It happens often, that a bridge built in an earlier time can not meet the requirements of the growing traffic in its original site, although its load carrying capacity did not decreased and in an other place, where the traffic is less intensive it would be suitable even for tens of years. The relocation of such structures depend mainly on the possibility of an economic realisation process. An economic process requires the application of method which ensure the movement of the possible largest units of structure (or the movement of the structure as a whole).

The case presented here shows such a relocation of a Tisza-bridge for a distance of about 100 km on the same river. The economic solution became possible by the application of up to date hydraulic tools and computerised on-line measurement supervision.